

IKA

designed for scientists



CBC ROTAVISC me-vi Package

/// Data Sheet

The viscosity of most liquids depends on the temperature. To obtain reliable measurement results, accurate temperature control is crucial. The CBC ROTAVISC me-vi Package is the perfect solution for precise viscosity measurement of temperature-dependent samples in the laboratory.

The ready-to-connect package combines the ROTAVISC me-vi rotational viscometer with the CBC VISC lite heating and cooling bath circulator. The sample is measured directly in the heating bath under controlled conditions.

ROTAVISC me-vi is a high-performance rotational viscometer for applications in a measuring range from 100 -

40,000,000 mPas.

The CBC VISC lite heating and cooling bath circulator was specially developed for use with IKA viscometers. It covers a temperature range from -25 °C to 125 °C and offers space for two standard beakers (600 ml). This allows a second sample to be pre-tempered during the measurement. Equipped with natural refrigerant R290, the CBC VISC lite is a sustainable and environmentally friendly alternative.

YOUR BENEFITS:

- Save time: A second beaker (600 ml) can be pre-tempered during the measurement.
- Perfect results: Optimized water flow management in the insulated bath for fast and precise temperature control.
- Improved ecological footprint: Equipped with the environmentally friendly natural refrigerant R290.
- Flexible application: Thanks to the external pump connection, CBC VISC lite can also be used for heating standard vessels according to DIN for absolute viscosity definition with ELVAS spindles or double-walled beakers.
- Easy to maintain: The easily removable and cleanable air filter guarantees optimum performance.
- Perfect compatibility and automation: ROTAVISC and CBC VISC lite are compatible with the labworldsoft® laboratory software, enabling easy automation, control and documentation of measurement results.

Technical Data

| | |
|--|--------------------------------|
| Viscosity Measuring Range [mPas] | 40000000 |
| Viscosity Accuracy (FSR) [%] | 1 |
| Viscosity Repeatability (FSR) [%] | 0.2 |
| Spring torque [mNm] | 0.7187 |
| Guard rail | me-vi |
| Measuring spindle series | SP set-2 |
| Motor rating output [W] | 4.8 |
| Overload protection | yes |
| Direction of rotation | right |
| Display | TFT |
| Speed display | TFT |
| Speed range [rpm] | 0.01 - 200 |
| Setting accuracy speed [rpm] | ±0.01 |
| Speed adjustment | TFT |
| Torque display | yes |
| Torque measurement | yes |
| Timer | yes |
| Timer display | TFT |
| Time setting range [min] | 0.017 - 6000 |
| Temperature measurement resolution [K] | 0.1 |
| Working temperature display | TFT |
| Connection for ext. temperature sensor | PT 100 |
| Graph function | yes |
| Operating mode | timer and continuous operation |
| Calibration option | yes |
| Touch function | yes |
| Permitted density [kg/dm ³] | 9999 |
| Working temperature [°C] | -100 - 300 |
| Fastening on stand | extension arm |
| Support rod diameter (with integrated fastening on stand) [mm] | 16 |
| Telescope stand stroke [mm] | 200 |
| Plug-in coupling (Ø) [mm] | 12 |
| Basic container volume [ml] | 600 |
| Stand | Rotastand |
| Stroke max. [mm] | 61 |
| Diameter [mm] | 16 |
| Dynamic load [kg] | 5 |
| Dimensions (W x H x D) [mm] | 351 x 629 x 372 |
| Weight [kg] | 7.1 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 40 |
| RS 232 interface | yes |
| USB interface | USB-B |
| Voltage [V] | 100 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 24 |
| Power input standby [W] | 1.6 |



designed for scientists

| | |
|--------------------------|------|
| DC Voltage [V=] | 24 |
| Current consumption [mA] | 1000 |