

Test weights and boxes

Class F1



Milligram weights,
flat polygonal sheet



Individual weights/
Weight sets,
ECO shape



Individual weights/
Weight sets,
knob shape



Test weights (10 – 50 kg),
polished stainless steel,
KERN 327-141 ff, optional:
Wooden box



Block weight,
polished stainless steel



Plastic box,
lined, for
individual
weights
≤ 200 g



Plastic box,
lined, for
individual
weights
≥ 500 g



Aluminium protected box, lined,
for individual weights



Wooden box, lined,
for individual weights ≤ 500 g



Wooden box, lined,
for individual weights ≥ 1 kg



Milligram weight
set in plastic box
(328-22)



Milligram weight
set in aluminium
protected box,
lined (328-226)



Plastic case, lined
for weight sets, ECO shape/
knob shape






Aluminium protected case, lined,
for weight sets ECO shape/
knob shape



Wooden case, lined,
for weight sets ECO shape/
knob shape




Class F1 - Milligram weights, flat polygonal sheet

Test weight material: stainless steel

Weight	Tol +/- mg	Milligram weight, flat polygonal sheet	Plastic box	Aluminium protected box	Wooden box	DAkkS certificate
		KERN	KERN 	KERN 	KERN 	KERN
1 mg	0,020	328-01	347-009-400	317-009-600	338-090-200	962-451
2 mg	0,020	328-02	347-009-400	317-009-600	338-090-200	962-452
5 mg	0,020	328-03	347-009-400	317-009-600	338-090-200	962-453
10 mg	0,025	328-04	347-009-400	317-009-600	338-090-200	962-454
20 mg	0,03	328-05	347-009-400	317-009-600	338-090-200	962-455
50 mg	0,04	328-06	347-009-400	317-009-600	338-090-200	962-456
100 mg	0,05	328-07	347-009-400	317-009-600	338-090-200	962-457
200 mg	0,06	328-08	347-009-400	317-009-600	338-090-200	962-458
500 mg	0,08	328-09	347-009-400	317-009-600	338-090-200	962-459


Class F1 - Individual weights, ECO shape or knob shape

Test weight material: stainless steel polished

Weight	Tol +/- mg	Individual weight, ECO shape	Individual weight, knob shape	Plastic box	Aluminium protected box	Wooden box	DAkkS certificate
		KERN	KERN	KERN 	KERN 	KERN 	KERN
1 g	0,10	326-01	327-01	347-030-400	317-010-600	317-010-100	962-431
2 g	0,12	326-02	327-02	347-030-400	317-020-600	317-020-100	962-432
5 g	0,16	326-03	327-03	347-030-400	317-030-600	317-030-100	962-433
10 g	0,20	326-04	327-04	347-050-400	317-040-600	317-040-100	962-434
20 g	0,25	326-05	327-05	347-050-400	317-050-600	317-050-100	962-435
50 g	0,30	326-06	327-06	347-070-400	317-060-600	317-060-100	962-436
100 g	0,50	326-07	327-07	347-070-400	317-070-600	317-070-100	962-437
200 g	1,00	326-08	327-08	347-080-400	317-080-600	317-080-100	962-438
500 g	2,50	326-09	327-09	347-090-400	317-090-600	317-090-100	962-439
1 kg	5,00	326-11	327-11	347-110-400	317-110-600	317-110-100	962-441
2 kg	10	326-12	327-12	347-120-400	317-120-600	317-120-100	962-442
5 kg	25	326-13	327-13	347-130-400	317-130-600	317-130-100	962-443
10 kg	50	326-14	327-14	347-140-400	317-140-600	317-140-100	962-444
20 kg	100	-	327-15	-	317-150-600	317-150-100	962-445
50 kg	250	-	327-16	-	317-160-600	317-160-100	962-446


Class F1 - Block weights

Block weight material: stainless steel polished

Weight	Tol +/- mg	Block weight	Aluminium protected case	DAkkS certificate
		KERN	KERN 	KERN
5 kg	25	326-36	346-060-600	962-443
10 kg	50	326-37	346-070-600	962-444
20 kg	100	326-38	346-080-600	962-445
50 kg	250	326-39	346-090-600	962-446




Class F1 - Test weights, stackable

Test weight material: stainless steel polished

Weight	Tol +/- mg	Test weight	Wooden case	DAkkS certificate
		KERN	KERN 	KERN
10 kg	50	327-141	337-141-100	962-444
20 kg	100	327-151	337-151-100	962-445
50 kg	250	327-161	337-161-100	962-446




Class F1 - Weight sets, ECO shape

Test weight material: Milligramm weights stainless steel, Individual weights: polished stainless steel

Weight sets	ECO shape in plastic case	ECO shape in aluminium protected case	ECO shape in wooden case	DAkkS certificate
	KERN 	KERN 	KERN 	
1 mg - 500 mg	328-22	328-226	-	962-450
1 mg - 50 g	325-024	325-026	325-022	962-401
1 mg - 100 g	325-034	325-036	325-032	962-402
1 mg - 200 g	325-044	325-046	325-042	962-403
1 mg - 500 g	325-054	325-056	325-052	962-404
1 mg - 1 kg	325-064	325-066	325-062	962-405
1 mg - 2 kg	325-074	325-076	325-072	962-406
1 mg - 5 kg	325-084	325-086	325-082	962-407
1 mg - 10 kg	-	325-096	325-092	962-408
1 g - 50 g	326-024	326-026	326-022	962-415
1 g - 100 g	326-034	326-036	326-032	962-416
1 g - 200 g	326-044	326-046	326-042	962-417
1 g - 500 g	326-054	326-056	326-052	962-418
1 g - 1 kg	326-064	326-066	326-062	962-419
1 g - 2 kg	326-074	326-076	326-072	962-420
1 g - 5 kg	326-084	326-086	326-082	962-421
1 g - 10 kg	-	326-096	326-092	962-422

Class F1 - Weight sets, knob shape

Test weight material: Milligramm weights stainless steel, Individual weights: polished stainless steel

Weight sets	Knob shape in plastic case	Knob shape in aluminium protected case	Knob shape in wooden case	DAkkS certificate
	KERN 	KERN 	KERN 	
1 mg - 500 mg	328-22	328-226	-	962-450
1 mg - 50 g	323-024	323-026	323-02	962-401
1 mg - 100 g	323-034	323-036	323-03	962-402
1 mg - 200 g	323-044	323-046	323-04	962-403
1 mg - 500 g	323-054	323-056	323-05	962-404
1 mg - 1 kg	323-064	323-066	323-06	962-405
1 mg - 2 kg	323-074	323-076	323-07	962-406
1 mg - 5 kg	323-084	323-086	323-08	962-407
1 mg - 10 kg	-	323-096	323-09	962-408
1 g - 50 g	324-024	324-026	324-02	962-415
1 g - 100 g	324-034	324-036	324-03	962-416
1 g - 200 g	324-044	324-046	324-04	962-417
1 g - 500 g	324-054	324-056	324-05	962-418
1 g - 1 kg	324-064	324-066	324-06	962-419
1 g - 2 kg	324-074	324-076	324-07	962-420
1 g - 5 kg	324-084	324-086	324-08	962-421
1 g - 10 kg	-	324-096	324-09	962-422

KERN Pictograms

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 Network interface: For connecting the scale to an Ethernet network	 Suspended weighing: Load support with hook on the underside of the balance
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required	 KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	 Battery operation: Ready for battery operation. The battery type is specified for each device
 Easy Touch: Suitable for the connection, data transmission and control through PC or tablet.	 Rechargeable battery pack: Rechargeable set	
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 GLP/ISO log: The balance displays weight, date and time, independent of a printer connection	 Universal plug-in power supply: with universal input and optional input socket adapters for A) EU, CH, GB B) EU, CH, GB, USA C) EU, CH, GB, USA, AUS
 Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 GLP/ISO log: With weight, date and time. Only with KERN printers.	 Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
 KERN Universal Port (KUP): allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 Integrated power supply unit: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 Data interface RS-232: To connect the balance to a printer, PC or network	 Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate
 USB data interface: To connect the balance to a printer, PC or other peripherals	 Totalising level A: The weights of similar items can be added together and the total can be printed out	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	 Percentage determination: Determining the deviation in % from the target value (100 %)	 Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
 WiFi data interface: To transfer data from the balance to a printer, PC or other peripherals	 Weighing units: Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details	 Verification possible: The time required for verification is specified in the pictogram
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram
 Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements	 Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Factory calibration (ISO): The time required for Factory calibration is shown in days in the pictogram
 Interface for second balance: For direct connection of a second balance	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
		 Pallet shipment: The time required for internal shipping preparations is shown in days in the