

# Test weights and boxes

## Classes M2 · M3



Individual weights/Weight sets,  
knob shape, stainless steel



Individual weights/Weight sets,  
knob shape, lacquered cast iron



Block weights,  
lacquered cast iron



Plastic box, lined,  
for individual weights



Aluminium protected box,  
lined, for individual weights



Wooden box, not lined, for  
individual weights  $\leq 500$  g,  
not appropriate for  
cast iron weights



Wooden box, not lined, for  
individual weights  $\geq 1$  kg,  
not appropriate for  
cast iron weights



Aluminium protected case,  
lined, for block weights



Aluminium protected case, lined, for weight  
sets knob shape, finely turned stainless steel,  
not appropriate for cast iron weights






Wooden case, for weight sets, knob shape,  
finely turned stainless steel



Wooden block, for weight sets, knob shape,  
lacquered cast iron


### Class M2 · Individual weights, knob shape

Test weight material: finely turned stainless steel

Weight	Tol +/- mg	Individual weight, knob shape	Plastic box	Aluminium protected box	Wooden box	DAkkS certificate
		KERN	KERN 	KERN 	KERN 	KERN
1 g	3	357-01	347-030-400	317-010-600	337-010-200	962-631
2 g	4	357-02	347-030-400	317-020-600	337-020-200	962-632
5 g	5	357-03	347-030-400	317-030-600	337-030-200	962-633
10 g	6	357-04	347-050-400	317-040-600	337-040-200	962-634
20 g	8	357-05	347-050-400	317-050-600	337-050-200	962-635
50 g	10	357-06	347-070-400	317-060-600	337-060-200	962-636
100 g	16	357-07	347-070-400	317-070-600	337-070-200	962-637
200 g	30	357-08	347-080-400	317-080-600	337-080-200	962-638
500 g	80	357-09	347-090-400	317-090-600	337-090-200	962-639
1 kg	160	357-11	347-110-400	317-110-600	337-110-200	962-641
2 kg	300	357-12	347-120-400	317-120-600	337-120-200	962-642
5 kg	800	357-13	347-130-400	317-130-600	337-130-200	962-643
10 kg	1600	357-14	347-140-400	317-140-600	337-140-200	962-644



### Class M2 · Block weights

Block weight material: lacquered cast iron, surface and edges machined or unmachined (ECO)

Weight	Tol +/- g	Block weight	ECO block weight	Aluminium protected box	DAkkS certificate
		KERN	KERN	KERN 	KERN
5 kg	0,8	356-86	356-76	346-060-600	962-643
10 kg	1,6	356-87	356-77	346-070-600	962-644
20 kg	3,0	356-88	356-78	346-080-600	962-645
50 kg	8,0	356-89	356-79	346-090-600	962-646




### Class M2 · Weight sets, knob shape

Test weight material: finely turned stainless steel

Weight	Knob shape, in aluminium protected case	Knob shape, in wooden case	DAkkS certificate
	KERN 	KERN 	KERN
1 g - 50 g	354-026	354-02	962-615
1 g - 100 g	354-036	354-03	962-616
1 g - 200 g	354-046	354-04	962-617
1 g - 500 g	354-056	354-05	962-618
1 g - 1 kg	354-066	354-06	962-619
1 g - 2 kg	354-076	354-07	962-620
1 g - 5 kg	354-086	354-08	962-621
1 g - 10 kg	354-096	354-09	962-622

### Class M3 · Individual weights, knob shape

Test weight material: finely turned stainless steel

Weight	Tol +/- mg	Individual weight, knob shape	Plastic box	Aluminium protected box	Wooden box	DAkkS certificate
		KERN	KERN 	KERN 	KERN 	KERN
1 g	10	367-01	347-030-400	317-010-600	337-010-200	962-631
2 g	12	367-02	347-030-400	317-020-600	337-020-200	962-632
5 g	16	367-03	347-030-400	317-030-600	337-030-200	962-633
10 g	20	367-04	347-050-400	317-040-600	337-040-200	962-634
20 g	25	367-05	347-050-400	317-050-600	337-050-200	962-635
50 g	30	367-06	347-070-400	317-060-600	337-060-200	962-636
100 g	50	367-07	347-070-400	317-070-600	337-070-200	962-637
200 g	100	367-08	347-080-400	317-080-600	337-080-200	962-638
500 g	250	367-09	347-090-400	317-090-600	337-090-200	962-639
1 kg	500	367-11	347-110-400	317-110-600	337-110-200	962-641
2 kg	1000	367-12	347-120-400	317-120-600	337-120-200	962-642

### Class M3 · Individual weights, knob and cylindrical shape


Test weight material: lacquered cast iron

Weight	Tol +/- g	Individual weight, knob and cylindrical shape	DAkkS certificate
		KERN	KERN
100 g*	0,05	366-91	962-637
200 g*	0,10	366-92	962-638
500 g**	0,25	366-93	962-639
1 kg**	0,50	366-94	962-641
2 kg**	1,0	366-95	962-642
5 kg**	2,5	366-96	962-643
10 kg**	5,0	366-97	962-644



### Class M3 · Block weights

Block weight material: lacquered cast iron, surface and edges machined or unmachined (ECO)

Weight	Tol +/- g	Block weight	ECO block weight	Aluminium protected box	DAkkS certificate
		KERN	KERN	KERN 	KERN
5 kg	2,5	366-86	366-76	346-060-600	962-643
10 kg	5,0	366-87	366-77	346-070-600	962-644
20 kg	10	366-88	366-78	346-080-600	962-645
50 kg	25	366-89	366-79	346-090-600	962-646

### Class M3 · Weight sets, knob and cylindrical shape

Test weight material: ≤ 50 g stainless steel, ≥ 100 g lacquered cast iron

Weight	Knob and cylindrical shape, in wooden block	DAkkS certificate
	KERN	KERN
1 g - 1 kg	362-96	962-619
1 g - 2 kg	362-97	962-620
1 g - 5 kg	362-98	962-621
1 g - 10 kg	362-99	962-622



# KERN Pictograms

 <b>Internal adjusting:</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 <b>Network interface:</b> For connecting the scale to an Ethernet network	 <b>Suspended weighing:</b> Load support with hook on the underside of the balance
 <b>Adjusting program CAL:</b> For quick setting up of the balance's accuracy. External adjusting weight required	 <b>KERN Communication Protocol (KCP):</b> It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device
 <b>Easy Touch:</b> Suitable for the connection, data transmission and control through PC or tablet.	 <b>Rechargeable battery pack:</b> Rechargeable set	 <b>Rechargeable battery pack:</b> Rechargeable set
 <b>Memory:</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 <b>GLP/ISO log:</b> The balance displays weight, date and time, independent of a printer connection	 <b>Universal plug-in power supply:</b> with universal input and optional input socket adapters for A) EU, CH, GB B) EU, CH, GB, USA C) EU, CH, GB, USA, AUS
 <b>Alibi memory:</b> Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 <b>GLP/ISO log:</b> With weight, date and time. Only with KERN printers.	 <b>Plug-in power supply:</b> 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
 <b>KERN Universal Port (KUP):</b> allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort	 <b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight	 <b>Integrated power supply unit:</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 <b>Data interface RS-232:</b> To connect the balance to a printer, PC or network	 <b>Recipe level A:</b> The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 <b>Weighing principle: Strain gauges</b> Electrical resistor on an elastic deforming body
 <b>RS-485 data interface:</b> To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 <b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 <b>Weighing principle: Tuning fork</b> A resonating body is electromagnetically excited, causing it to oscillate
 <b>USB data interface:</b> To connect the balance to a printer, PC or other peripherals	 <b>Totalising level A:</b> The weights of similar items can be added together and the total can be printed out	 <b>Weighing principle: Electromagnetic force compensation</b> Coil inside a permanent magnet. For the most accurate weighings
 <b>Bluetooth* data interface:</b> To transfer data from the balance to a printer, PC or other peripherals	 <b>Percentage determination:</b> Determining the deviation in % from the target value (100 %)	 <b>Weighing principle: Single cell technology:</b> Advanced version of the force compensation principle with the highest level of precision
 <b>WiFi data interface:</b> To transfer data from the balance to a printer, PC or other peripherals	 <b>Weighing units:</b> Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details	 <b>Verification possible:</b> The time required for verification is specified in the pictogram
 <b>Control outputs (optocoupler, digital I/O):</b> To connect relays, signal lamps, valves, etc.	 <b>Weighing with tolerance range:</b> (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 <b>DAkkS calibration possible (DKD):</b> The time required for DAkkS calibration is shown in days in the pictogram
 <b>Analogue interface:</b> to connect a suitable peripheral device for analogue processing of the measurements	 <b>Hold function:</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 <b>Factory calibration (ISO):</b> The time required for Factory calibration is shown in days in the pictogram
 <b>Interface for second balance:</b> For direct connection of a second balance	 <b>Protection against dust and water splashes IPxx:</b> The type of protection is shown in the pictogram.	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram
		 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the