



## Personal floor scale KERN MPC

Compact personal floor scale – with EC type approval and approval for professional medical use in medical diagnostics



KERN MPC 250K100M

Special obesity model  
KERN MPC 300K-1LM

## Personal floor scale KERN MPC



### Features

- Verification class III (verification is optional)
- Approved as a medical device according to 93/42/EEC
- The bestseller for doctor's surgeries, chemists and hospitals
- Robust design for daily use in a professional environment
- Easy and hygienic cleaning
- Secure and non-slip positioning with height-adjustable rubber feet
- Level indicator to level the balance precisely
- KERN MPC 300K-1LM: Version with [Max] = 300 kg and larger weighing plate. Specially suitable for weighing overweight patients who are in the obese category
- 1 KERN MPC 300K-1LM: Sturdy handle for easy transportation of the scale
- 2 Flexible positioning of display device, e.g. free-standing or mounted to the wall. Wall mount for display device standard
- 3 Large platform with non-slip and wear-resistant surface made of plastic, to provide a secure footing for patients
- High resolution readability: Readability [d] can be increased by one decimal place for 5 sec. by the touch of a key
- BMI function to determine underweight/normal weight/surplus weight

- Hold function: When patients do not stand completely still, a stable weight is calculated using an average weight and this is then "frozen". This means that you have sufficient time to attend to the patient first and then take the weight reading in peace
- Mother and child function: the parent's weight will be taken and then the scale will be reset to zero at the push of a button. Afterwards then the parent and baby can be weighed together. The weight of the child will now be shown on the display. This is particularly good for infants, as this way they can be cradled, safe and sound, in the arms of the parent while being weighed
- GLP/ISO report, printout of weight value, BMI etc. with date and time. FLP/GMP-compliant print form in DE, EN, FR, only in combination with RS-232 interface cable KERN CFS-A01 + MPC-A01 and printer KERN YKB-01N
- Battery- or mains-powered, rechargeable battery operation optional
- Protective working cover included with delivery

### Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions of display device WxDxH 200x130x60 mm
- Cable length of display device approx. 1,8 m
- Battery operation possible, 6x1.5 V AA not included, operating time up to 20 h
- Mains adapter external, standard

### Accessories

- Protective working cover over the display device, scope of delivery: 5 items, KERN MBC-A06S05
- Cleaning cloths, alcohol-free cloths for disinfectant wiping, quick acting, based on modern quaternary ammonium compounds and effective against papova viruses. Particularly gentle on materials, and very well suited for disinfecting products which are sensitive to alcohol. Fulfill the legal requirements for occupational safety in accordance with TRGS 525/540. Packaging contents 100 pcs., size 20x22 cm per cloth, KERN MYC-01
- Internal rechargeable battery pack, operating time up to 40 h without backlight, charging time approx. 12 h, KERN MBC-A08
- External mains adapter, 100 V - 240 V, Standard EU, CH, UK, KERN YKA-43
- External mains adapter, 100 V - 240 V, Standard EU, KERN YKA-44
- RS-232 data interface, must be ordered at purchase, KERN MPC-A01
- Interface cable RS-232 to connect an external device, KERN CFS-A01


#### STANDARD



#### OPTION



#### FACTORY



Model	Weighing capacity	Readability	Verification value	Weighing plate	Net weight approx.	Mandatory by law Verification
	[Max] kg	[d] kg	[e] kg	mm	kg	
<b>MPC 250K100M</b>	250	0,1	0,1	365x370x80	9	965-129
<b>MPC 300K-1LM</b>	300	0,1	0,1	400x500x120	10	965-129

\* Within the EU, official verification is mandatory by law for scales that are intended for use as a medical device. Please add this to your order. We require the location of use and the post code for the verification.



### Adjusting program CAL:

For quick setting up of the balance's accuracy. External adjusting weight required



### Memory:

Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



### Data interface RS-232:

To connect the balance to a printer, PC or network



### RS-485 data interface:

To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible



### Bluetooth\* data interface:

To transfer data from the balance to a printer, PC or other peripherals



### WIFI data interface:

To transfer data from the balance to a printer, PC or other peripherals



### Control outputs

(optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.



### Statistics:

using the saved values, the device calculates statistical data, such as average value, standard deviation etc.



### PC Software:

to transfer the measurements from the device to a PC



### GLP/ISO log:

With date and time. Only with KERN printers



### KERN Communication Protocol (KCP):

It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems



### Piece counting:

Reference quantities selectable. Display can be switched from piece to weight



### Totalising level A:

The weights of similar items can be added together and the total can be printed out



### Weighing units:

Can be switched to e.g. nonmetric units. Please refer to website for more details



### Weighing with tolerance range

(Check weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model



### ZERO:

Resets the display to "0"



### Hold function:

When patients do not stand, sit or lie completely still, a stable weight is calculated using an average weight



### Hold function:

When the weighing conditions are unstable, a stable weight is calculated as an average value



### Protection against dust and water splashes IPxx:

The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013



### Suspended weighing:

Load support with hook on the underside of the balance



### Battery operation:

Ready for battery operation. The battery type is specified for each device



### Rechargeable battery pack:

Rechargeable set



### Battery operation rechargeable

Prepared for a rechargeable battery operation



### Universal plug-in power supply:

with universal input and optional input socket adapters for  
A) EU, CH  
B) EU, CH, GB, USA



### Plug-in power supply:

230V/50Hz in standard version for EU. On request GB, AUS or USA version available



### Integrated power supply unit:

Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request



### Weighing principle: Strain gauges

Electrical resistor on an elastic deforming body



### Peak hold function:

capturing a peak value within a measuring process



### Push and Pull:

the measuring device can capture tension and compression forces



### Integrated scale:

In the eyepiece



### 360° rotatable microscope head



### Monocular Microscope:

For the inspection with one eye



### Binocular Microscope:

For the inspection with both eyes



### Trinocular Microscope:

For the inspection with both eyes and the additional option for the connection of a camera



### Abbe Condenser:

With high numerical aperture for the concentration and the focusing of light



### Halogen illumination:

For pictures bright and rich in contrast



### LED illumination:

Cold, energy-saving and especially long-life illumination



### Fluorescence illumination for compound microscopes:

With 100 W mercury lamp and filter



### Fluorescence illumination for compound microscopes:

With 3 W LED illumination and filter



### Phase contrast unit:

For a higher contrast



### Darkfield condenser/unit:

For a higher contrast due to indirect illumination



### Polarising unit:

To polarise the light



### Infinity system:

Infinity corrected optical system



### Automatic temperature compensation:

For measurements between 10 °C and 30 °C



### Verification possible:

The time required for verification is specified in the pictogram



### Package shipment:

The time required for internal shipping preparations is shown in days in the pictogram



### Pallet shipment:

The time required for internal shipping preparations is shown in days in the pictogram

\*The Bluetooth\* word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.