

Digital microscope sets KERN OZM-S · OZP-S



OZM-5 with camera



OZP-5 with camera



OZP-5 with tablet

First-class optics as well as strong illumination combined with a high level of flexibility and digital tools

**Features** **Technical data**

- Stereomicroscopes from the OZM and OZP range are now also available to you as a comprehensive digital solution for your live investigations. Optionally available with an mounted tablet or C-mount camera. Naturally, the appropriate C-mount adapter is included with the delivery
- The mounted KERN ODC 241 tablet-camera has been specially developed for simple, convenient and direct investigation of the sample on the screen. Ideally suited for school pupils and students in education or for demonstration purposes in the laboratory
- The mounted C-mount camera is available in different versions and can be used anywhere
- For detailed information on the individual components, see the relevant product description of the individual item
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of the delivery

- Optical system: Greenough optics
- Brightness adjustable (separate)
- Light distribution: 100:0
- Diopter adjustment: Both-sided
- Net weight approx. 5,5 kg
- Eyepiece: HSWF 10×/∅ 23 mm
- Stand: Pillar style
- Illumination: 3 W LED (incident + transmitted)































- OZM-5**
- Tube 45° inclined
  - Magnification ratio: 6,4:1
  - Interpupillary distance 52 – 76 mm
  - Overall dimensions W×D×H 330×285×440 mm
  - Field of view: ∅ 32,8 – 5,1 mm
  - Objective: 0,7× – 4,5×

- OZP-5**
- Tube: 35° inclined
  - Magnification ratio: 9,2:1
  - Interpupillary distance 52 – 76 mm
  - Overall dimensions W×D×H 330×285×470 mm
  - Field of view: ∅ 38,3 – 4,2 mm
  - Objective: 0,6× – 5,5×

**Model**

Standard configuration (camera)

	Included camera	Resolution camera	Interface	Sensor	Details microscope, camera
<b>OZM 544C825</b>	ODC 825	5 MP	USB 2.0 (6,8 – 55 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 52, 86
<b>OZM 544C832</b>	ODC 832	5 MP	USB 3.0 (14,2 – 101,2 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 52, 86
<b>OZP 558C825</b>	ODC 825	5 MP	USB 2.0 (6,8 – 55 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 86
<b>OZP 558C832</b>	ODC 832	5 MP	USB 3.0 (14,2 – 101,2 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 86
<b>OZP 558T241</b>	ODC 241	5 MP	WiFi, USB 2.0, HDMI, SD (15 – 30 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 54, 90

- 
**360° rotatable microscope head**
- 
**Monocular Microscope**  
 For the inspection with one eye
- 
**Binocular Microscope**  
 For the inspection with both eyes
- 
**Trinocular Microscope**  
 For the inspection with both eyes and the additional option for the connection of a camera
- 
**Abbe Condenser**  
 With high numerical aperture for the concentration and the focusing of light
- 
**Halogen illumination**  
 For pictures bright and rich in contrast
- 
**LED illumination**  
 Cold, energy-saving and especially long-life illumination
- 
**Incident illumination**  
 For non-transparent objects
- 
**Transmitting illumination**  
 For transparent objects
- 
**Fluorescence illumination**  
 For stereomicroscopes
- 
**Fluorescence illumination for compound microscopes**  
 With 100 W mercury lamp and filter
- 
**Fluorescence illumination for compound microscopes**  
 With 3 W LED illumination and filter
- 
**Phase contrast unit**  
 For a higher contrast
- 
**Darkfield condenser/unit**  
 For a higher contrast due to indirect illumination
- 
**Polarising unit**  
 To polarise the light
- 
**Infinity system**  
 Infinity corrected optical system
- 
**Zoom magnification**  
 For stereomicroscopes
- 
**Auto-focus**  
 For automatic control of the focus level
- 
**Parallel optical system**  
 For stereomicroscopes, enables fatigue-proof working
- 
**Integrated scale**  
 In the eyepiece
- 
**SD card**  
 For data storage
- 
**USB 2.0 digital camera**  
 For direct transmitting of the picture to a PC
- 
**USB 3.0 digital camera**  
 For direct transmitting of the picture to a PC
- 
**WiFi data interface:**  
 For transmitting of the picture to a mobile display device
- 
**HDMI digital camera**  
 For direct transmitting of the picture to a display device
- 
**PC software**  
 To transfer the measurements from the device to a PC.
- 
**Automatic temperature compensation**  
 For measurements between 10 °C and 30 °C
- 
**Protection against dust and water splashes IPxx:**  
 The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013
- 
**Battery operation**  
 Ready for battery operation. The battery type is specified for each device.
- 
**Battery operation rechargeable**  
 Prepared for a rechargeable battery operation
- 
**Plug-in power supply**  
 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
- 
**Integrated power supply unit**  
 Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
- 
**Package shipment**  
 The time required to manufacture the product internally is shown in days in the pictogram.

## ABBREVIATIONS

- C-Mount** Adapter for the connection of a camera to a trinocular microscope
- FPS** Frames per second
- H(S)WF** High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)
- LWD** Long Working Distance
- N.A.** Numerical Aperture
- SLR camera** Single-Lens Reflex camera
- SWF** Super Wide Field (Field number at least  $\varnothing$  23 mm for 10 $\times$  eyepiece)
- W.D.** Working Distance
- WF** Wide Field (Field number up to  $\varnothing$  22 mm for 10 $\times$  eyepiece)