

# MA37

## Fully Automatic Infrared Moisture Analyzer for Daily Routine Operation



### Benefits

- High-speed measurements
- Effortless cleaning
- User-friendly operation
- Status light for display of measurement progress

### Product Overview

The MA37 is the new Sartorius basic analyzer for moisture determination. It operates even faster and is easier to use than its predecessor MA35. In addition, it features a compact footprint and delivers highly accurate results. Moreover, its BetterClean design also enables effortless cleaning, and the convenient status light indicates the current progress of a measurement. The MA37 is therefore ideal for operations involving identical routine measurement tasks, guiding you step by step throughout moisture analysis.

# Product Information

## Applications

The MA37 moisture analyzer is designed for quick and reliable determination of the moisture content of liquids, pastes and solids using the thermogravimetric method. The MA37 is perfectly suited to daily recurring moisture analysis tasks, such as in production or incoming goods inspection.

## Performance

Fully automatic endpoint determination eliminates the inconvenience of time-consuming screening of shutoff parameters. The moisture analyzer monitors the drying process and ends the measurement once it detects a constant sample weight. The built-in weighing system with 1 mg resolution has been specially optimized for use in higher temperature ranges, delivering the required measurement accuracy. A high-performance metal tube heater heats the samples in the MA37. This heater unit is fast, extremely rugged and durable. Unlike glass heating lamps, such as infrared lamps or halogen heaters, it is especially resistant to dirt and vibration. The functionality of the MA37 can be verified at any time by running the built-in performance test with a ReproEasy pad.

# Technical Specifications

Max. weighing capacity	70 g
Reproducibility, typical	For initial sample weights of approx. > 1 g: $\pm 0.2\%$ For initial sample weights of approx. > 5 g: $\pm 0.05\%$
Readability	1 mg, 0.01%
Typical sample quantity	5 g - 15 g
Display modes for results	Moisture content in %M and g   dry weight in %S and g   ATRO (ratio) in %M/S
Temperature range and settings	40 °C - 200 °C, in increments of 1 °C Standby temperature selectable from 50 °C - 120 °C
Sample heating	Infrared metal heating elements
Heating programs	Standard drying, gentle drying, MA35 mode
Shutoff parameter	Choice of modes: <ul style="list-style-type: none"> <li>▪ Fully automatic</li> <li>▪ Semiautomatic mg (1 mg - 50 mg   5 sec. - 300 sec.)</li> <li>▪ Semiautomatic % (0.1% - 5.0%   5 sec. - 300 sec.)</li> <li>▪ Timer settings (02:00 - 99.59 min.)</li> <li>▪ Manual</li> </ul>
Access to sample chamber	Removable hood with wide opening angle; SoftClose mechanism
Measuring program	1 program saved in the non-volatile memory (user-definable method parameters)
Memory for data storage	Results are saved until the start of the next measurement
Operator guidance features	Intuitive user interface, including touch screen and easy-to-understand menu prompts
Languages selectable in menu	English set as the default; can be changed in the menu to Chinese, French, Italian, Japanese, Polish, Portuguese, Russian, Spanish and Turkish
Status light	Displays the status "analysis running / START," "analysis completed / STOP" or "analysis error"
Sample inspection	LED-illuminated sample chamber; inspection window with grid above the hood
Draft shield	Integrated draft shield
Cleaning	Removable hood, grid and sample chamber plate for easy cleaning in a laboratory dishwasher
Printout	<ul style="list-style-type: none"> <li>▪ Printout using the optional, internal printer YDP30; alternatively, the printer YDP20-OCE can be used with an adapter (YCC03-D09)</li> <li>▪ GLP-compliant, inalterable standard for printout of the results   paper-saving mode for short record</li> </ul>
Performance test	Menu function for testing the analyzer's performance using a ReproEasy pad
Monitoring and control of the accuracy of the analyzer as inspection, measuring and test equipment	External calibration using optional calibration weights; Temperature adjustment with optional adjustment set
Data interface	Mini USB port <ul style="list-style-type: none"> <li>▪ Automatic detection of the Sartorius printers YDP30 and YDP40</li> <li>▪ Direct data transfer to Microsoft® Office programs without any additional software</li> <li>▪ Programmable data output interval</li> <li>▪ SBI data transfer protocol</li> </ul>
Frequency	50   60 Hz
Power consumption	Max. 640 VA
Temperature range	10 °C - 30 °C
Housing dimensions (W + D + H)	215 + 400 + 210 mm (8.5" + 15.7" + 8.3")
Weight	Approx. 6.2 kg (approx. 13.6 lbs.)