

stakpure Ion exchange system DS 150 duo

stakpure

Pressure-resistant ion exchanger system from stakpure, the economical way to fully demineralised water. In a cartridge made of plastic, water flows over a mixed bed of special anion and cation resins and is thus fully desalinated or demineralised by the proven method of the ion exchanger process. The system is completed with an analogue conductivity meter for practical back wall mounting, wall mounting plate and hose set. Specially developed for medical practices, small laboratories and the production of battery water with a daily requirement of up to 10 litres, this system prevents, for example, streaks, stains or even corrosion on instruments. Ion exchange systems from stakpure meet all current standards such as DIN EN 13060, EN 285 and VDE 0510 and achieve a consistently high water quality.

Design and scope of delivery

2 x Pressure-resistant plastic housing

2 x 10" ion exchanger insert

Analogue conductivity meter AW 100

Wall mounting plate (pre-assembled)



Type DS	150 duo
Flow rate	50 l/h
Capacity at 10°GSG*	2 x 150 l
Pure water	quality 0.1 - 20 µS/cm
Water temperature	max. 30°C
Power supply	230 volts / 50-60 Hz
Pressure resistant	up to max. 6 bar
Dimensions	W 550 x H 440 x D 150 mm
Connection	R ¾" AG
Weight approx.	8,46 kg
Order no.	11015100
*Total salt content	
Order no. Spare cartridge set of 2	11015200