

Ductless fume hood 1200 mm - 2 Modules - for liquid - two openings

COMPLIANCE

NF X 15-211 Classe 1

ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics

- Draft standard EN 17242

BUT ALSO...

- Easy replacement of the active coal filter
- Low acoustic level
- Front control window to see immediately the filter
- NF X 15-211 compliant
- Delivered ready to use
- Lighting control allowing to survey the proper working of the fan
- Holes for the cables and fluid going through
- Glass side walls
- Ergonomic hand traps or trapezoidal opening



TECHNICAL FEATURES

| | | | |
|---------------------------------|-----------------------------|------------------------------|-----------------|
| Model | H122D+2C | Hour counter | included |
| Compliance | NF X 15-211 Classe 1 | Sampling outlet | included |
| Airflow (m/s) | 0,4 - 0,6 | Backwall transparent | included |
| Voltage (volts) | 220-240 | Melamine work-top | Option |
| Flow (m ³ /h) | 170 | Electrical power (W) | 63 |
| Openings for passages of cables | 4 | Sound power of the fan dB(A) | 60.00 |
| Anemometer | included | HS Code | 84146000 |
| Guide of chemicals adsorbed | included | | |

COMPLEMENTARY PRODUCTS

- Activated carbon filter for ammonia vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : AMM200)
- Activated carbon filter for organic and corrosive vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : CORG201)
- Activated carbon filter for formaldehyde vapors - for old fume hoods type 200, 201, 210 and 211 (Réf : FOR200)
- Activated carbon filter for organic vapors for H200 - H201 - H210 - H211 (Réf : ORG200)
- Containment sump and melamine work-top for H12 (Réf : BB12)
- Containment sump and tempered glass work-top for H12 (Réf : BV12)

OPTIONS

- Lighting for ductless fume hoods (Réf : LUMI)
- Table-cabinet for H12 (Réf : TA12)
- Trolley with adjustable shelf for H12 (Réf : TR12)
- Tubular table with feet for model H12 (Réf : TTF12)
- Tubular table with wheels for model H12 (Réf : TTR12)

| Model | External dimensions HxWxD (mm) | Internal dimensions HxWxD (mm) | Weight (kg) |
|----------|--------------------------------|--------------------------------|-------------|
| H122D+2C | 1160 x 1200 x 750 | 935 x 1145 x 700 | 44.00 |