

3035E



## 2 doors safety cabinet Type 30

### COMPLIANCE

EN 14470-1, FM 6050

### ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

### BUT ALSO...

- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Adjustable leveling feet for enhance stability
- Pedestal area under-driveable by a forklift by removing panel
- Tested and approved according to FM 6050



### TECHNICAL FEATURES

Model	<b>3035E</b>	Shipping dimensions HxWxD (mm)	<b>2200 x 1200 x 800</b>
Compliance	<b>EN 14470-1, FM 6050</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Cabinet materials	<b>Melamine wood structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>light grey RAL 7035</b>	Number of compartments	<b>1</b>
Number of doors	<b>2</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>	Containment sump in PVC	<b>option</b>
Hinges	<b>right &amp; left</b>	Grating	<b>option</b>
Door closure	<b>self-closing</b>	HS Code	<b>94036000</b>

### ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)

### OPTIONS

- Containment sump for 2-door cabinets Types 30, 60 & 90 (Réf : B235)
- Perforated cover plate for 2-door safety cabinets Types 30, 60 & 90 (Réf : C235)
- Retention shelf for 2-door safety cabinets Types 30, 60 & 90 (Réf : E35)
- Containment sump in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SB148)
- Protection shelf in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SE48)
- Sliding drawer for 2-door safety cabinets Types 30, 60 & 90 (Réf : T235)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3035E	1980 x 1115 x 550	1580 x 1050 x 420	250	1	3	50	210.00