

1- door tall safety cabinet Type 90

COMPLIANCE

EN 14470-1, EN 1363-1

ADVANTAGES

- EN 14470-1 and FM 6050 compliant
- Storage of flammables
- Tested 105 min - from outside to inside in accordance with standard EN14470-1
- Fire resistance 90 min - Tested and approved to standard EN 14470-1 and EN 1363-1

BUT ALSO...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory
- Adjustable shelves in height



TECHNICAL FEATURES

Model	794+E	Door closure	self-closing
Compliance	EN 14470-1, EN 1363-1	Shipping dimensions HxWxD (mm)	2150 x 1200 x 800
Cabinet materials	12/10th epoxy painted steel structure	Ventilation	Both inlet and outlet on the back wall of the cabinet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	1	Number of compartments	1
Doors type	swing doors	Containment sump	1
Hinges	right	HS Code	94032080

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump for 1-door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Retention shelf for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : E48)
- Containment sump in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SB148)
- Protection shelf in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SE48)
- Sliding drawer for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : T148)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
794+E	1950 x 635 x 620	1620 x 490 x 410	130	1	3	30	287.00