

794+LiX4



# Safety cabinet 90 min lithium batteries hight 1 door + 4 E48Li + Vig190

## COMPLIANCE

## ADVANTAGES

- Storage of flammables
- Storage of lithium-ion batteries
- Tested 105 min - from outside to inside in accordance with standard EN14470-1
- Inside to outside fire-stop construction E1180
- French manufacturing - CSR
- FM compliant
- Fire resistance 90 min - Tested and approved to standard EN 14470-1 and EN 1363-1

## BUT ALSO...

- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Reduce the risk of fire and explosion



## TECHNICAL FEATURES

Model	<b>794+LiX4</b>	Openings diameter (mm)	<b>100</b>
Number of doors	<b>1</b>	HS Code	<b>94032080</b>

## ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Containment sump for 1- door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Perforated shelf for 1-door safety cabinet (Réf : E48LI)
- Rack of 9 electrical outlets (Réf : PRISELI)
- Breakthrough for cable entry with fire-resistant cable (Réf : PEXTBALI)
- Rack of 6 electrical outlets equipped with a thermal-magnetic circuit breaker (Réf : PRISELICC)
- Rack of 8 electric outlets type F (Germany) (Réf : PRISELIF)
- Rack of 8 electrical outlets type J (Switzerland) (Réf : PRISELICH)
- Rack of 7 G-type electrical outlets (UK) (Réf : PRISELIUK)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
794+LiX4	1950 x 635 x 620	1620 x 490 x 410	0		0	80	287.00

