

795+900E

EN
14470-1FM
6050EN
1612190
HOMOLOGUÉE
APPROUVÉE
EN 14470-1105
CONCÉU SELON
LE DÉCRET
EN 14470-1

2- door tall safety cabinet Type 90

COMPLIANCE

EN 14470-1, EN 1363-1

ADVANTAGES

- EN 14470-1 and FM 6050 compliant
- Storage of flammables
- Fire resistance 90 min - Tested and approved to standard EN 14470-1 and EN 1363-1
- Tested 105 min - from outside to inside in accordance with standard EN14470-1

BUT ALSO...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory



TECHNICAL FEATURES

Model	795+900E	Door closure	self-closing
Compliance	EN 14470-1, EN 1363-1	Shipping dimensions HxWxD (mm)	2150 x 1200 x 800
Cabinet materials	12/10th epoxy painted steel structure	Ventilation	Both inlet and outlet on the back wall of the cabinet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	2	Number of compartments	1
Doors type	swing doors	HS Code	94032080
Hinges	right & left		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump for 2- door cabinets Types 60 & 90 W 900 mm (Réf : B235-900)
- Perforated cover plate for 2- door cabinets Types 60 & 90 W 900 mm (Réf : C235-900)
- Retention shelf for 2- door cabinets Types 60 & 90 W 900 mm (Réf : E235-900)
- Sliding drawer for 2- door cabinets Types 60 & 90 W 900 mm (Réf : T235-900)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
795+900E	1950 x 905 x 620	1620 x 765 x 410	200		0	0	420.00

